

Self-Check AIR™

A breath of fresh...

D-Tech's Self-Check AIR™ is a stand-alone kiosk system. Our RFID technology provides enhanced material protection and easy operation. Intuitive touch screen graphics assures rapid acceptance by your patrons.

Packaged in a durable, powder coated painted steel body and illuminated with a desktop approach at being a stand-alone Self-Check AIR™ with its ScreenRead™ technology will provide an excellent choice for your library with an aesthetically pleasing design for all patrons.

Features:

- Works with complete range of D-Tech 13.56 MHz RFID labels as well as items tagged with approved labels from book suppliers
- D-Tech's advanced digital radio frequency identification technology uses state of the art digitally enhanced "software to chip" technology to ensure superior read/write to the RFID label with false alarm-free protection
- Integrated barcode scanning for patron library cards is standard; options include biometrics and smartcards for patron identification
- Software supports check-out and returns plus renew functions, together with optional payment functions including coins, currency, smart cards and credit cards
- Integrated date due printer is included.
- Off-line mode is used for statistics and full cash audit.
- AdminTool™ allows network access to change or configure the installed system, to add the library's logo for example.
- Modular matching furniture is available.



Self-Check AIR™

A breath of fresh...



Specifications:

Unit

	Self-Check AIR™ 26"Kiosk	Self-Check AIR™ 42"Kiosk
Height	30" (760mm)	30" (760mm)
Width	24.8" (635 mm)	40.8" (1035mm)
Depth	17.3" (440mm)	21.3" (540mm)
Weight	88 lbs. (40kg)	106 lbs. (48kg)

Material:

Frame: Steel finished in white with white contrasting beveled edges.
 Body trim: Plexiglas décor panels with back lighting to compliment

Power Supply:

100 –120 VAC, 60 Hz.

Electronics:

MR101 USB connection to industrial touch screen PC [19"]
 5* star rated energy efficient PC

Installation Requirements

System

Self-Check AIR™ units are freestanding to fit the library décor with a minimal footplate. Available in different colors with cost options

Power and Data Supply

One per Self-Check – one 100-120 VAC double outlet, 15 amps.
 One per Self-Check – one single IP addressed network point adjacent to above power outlet

AFI/EAS

Recommended AFI mode supported for security switching but EAS bit also supported

Location

The Self-Check location and layout is to be detailed and decided upon by the RFID Project Manager in conjunction with the Library's RFID Team.

UL approved and FCC certified.

Self-Check AIR™ Part Number:
 Standard26"* Kiosk DT1020426R

*with patrons barcode and printer

Self-Check AIR™ Part Number:
 Premium 42"* Kiosk DT1020442R

*with patrons barcode and printer